




Inglewood Shelter Galvanised Steel Frame Open Sided



The Inglewood shelter is a free-standing, open fronted shelter designed for on site assembly, constructed from galvanised mild steel. Complete with a 4mm UV stabilised PETG clear sheet roof, and ½ side panels. Side-to side curved roof.

Suitable as a smoking shelter. Width of 3m, with lengths from 1-5m, extension bays can be added to achieve the desired shelter length.

Bolt down as standard.



Part Number	Description	Weight (kg)
138 000 410	Inglewood Shelter 1m	214kg
138 000 412	Inglewood Shelter 2m	306kg
138 000 414	Inglewood Shelter 3m	398kg
138 000 416	Inglewood Shelter 4m	490kg
138 000 418	Inglewood Shelter 5m	585kg
138 000 411	Inglewood Shelter 1m extension bay	
138 000 413	Inglewood Shelter 2m extension bay	
138 000 415	Inglewood Shelter 3m extension bay	
138 000 417	Inglewood Shelter 4m extension bay	
138 000 419	Inglewood Shelter 5m extension bay	

Product details

- Height - 2090mm clearance, 2513mm overall
- Width - 3147mm overall
- Length - 1m, 2m, 3m, 4m, 5m and extensions
- Square flange plate - 140mm x 140mm x 10mm
- Each flange plate requires 4 bolts
- 4mm UV stabilised PETG clear sheet panels

Installation & use

This product is guaranteed for 12 months (if installed and used correctly)
Each shelter leg requires bolting down to a suitable concrete surface, using expanding anchor bolts
The area surrounding the installation must be flat and level with no nearby surface irregularities or gradient changes
On-site assembly requires construction skill

